


We Make Solar Evolve

ELiTe MONO

Monocrystalline Module

ET-M660290WB 290W

ET-M660280WB 280W



Rich Product Portfolio & Innovative Product Strategy, satisfy customer needs to the best, and keep the customers' overall costs to the lowest.



High Conversion Efficiency

Industry-leading processing techniques realize great module efficiency to a maximum of 17.83%, steady power output guaranteed.



Anti-reflective Coating and Reduce O&M Costs

Easier to clean by rainwater to remove dirt on the glass surface, making higher power output and lower maintenance costs.



0 to +5W Positive Tolerance

Gain more power yields than expected.




Excellent Loading Capability

2400Pa wind loads, 5400Pa snow loads.
Durable and long-lasting.



Top-quality & Trustworthy Product

Rigorous Quality Management System built.
Multiple internationally recognized PV industry standard certifications attained.



25 25-year performance warranty

10 10-year warranty on materials and workmanship

IEC 61215 Ed.2
IEC 61730
IEC 61701
IEC 62716
UL 1703



CONFORMS TO UL STD. 1703
CERTIFIED TO ULCDORD STD.C 1703-01



ET

Towards Excellence

www.etsolar.com

M/ET-PD-EN-AP2017V1-T

ELECTRICAL SPECIFICATIONS (STC)

Model Type	ET-M660290WB	ET-M660280WB
Peak Power (Pmax)	290W	280W
Module Efficiency	17.83%	17.21%
Maximum Power Voltage (Vmp)	32.12V	31.43V
Maximum Power Current (Imp)	9.03A	8.91A
Open Circuit Voltage (Voc)	39.68V	39.12V
Short Circuit Current (Isc)	9.59A	9.29A
Power Tolerance	0 to +5W	
Operating Temperature	- 40 ~ + 85°C	
Maximum System Voltage	DC 1000V	
Nominal Operating Cell Temperature	45±2°C	
Fire Safety	Class C	
Maximum Series Fuse Rating	20A	

ELECTRICAL SPECIFICATIONS (NOCT)

Model Type	ET-M660290WB	ET-M660280WB
Peak Power (Pmax)	214W	205.6W
Maximum Power Voltage (Vmp)	29.8V	29.3V
Maximum Power Current (Imp)	7.18A	7.01A
Open Circuit Voltage (Voc)	36.7V	35.9V
Short Circuit Current (Isc)	7.74A	7.5A

MECHANICAL SPECIFICATIONS

Cell Type	156.75mm x 156.75mm
Number of Cells	60 cells in series
Weight	18.5 kg (40.79 lbs)
Dimension	1640×992×35mm (64.57×39.06×1.38 inch)
Max Load	5400 Pascals (112 lb/ft²)
Junction Box	IP67 rated
Connector	TLCABLE01 Or QC4.10 Or Genuine MC4 Or PV-KST4/xy, PV-KBT4/xy
EN50521	Or PV-CF-S 2,5-6(+/-) PV-CM-S 2,5-6(-)

TEMPERATURE COEFFICIENT


Temp. Coeff. of Isc (TK Isc)	0.05% /°C
Temp. Coeff. of Voc (TK Voc)	-0.30% /°C
Temp. Coeff. of Pmax (TK Pmax)	-0.42% /°C

PACKING MANNER

Container	40' HQ
Pieces per Pallet	30
Pieces per Container	840


PHYSICAL CHARACTERISTICS

Unit:mm (inch)




ELECTRICAL CHARACTERISTICS

Temperature Dependence of Isc, Voc and Pmax



Irradiance Dependence of Isc, Voc and Pmax (AM1.5, Cell Temperature 25°C)



Note: the specifications are obtained under the Standard Test Conditions (STCs): 1000 W/m² solar irradiance, 1.5 Air Mass, and cell temperature of 25°C. The NOCT is obtained under the Test Conditions: 800 W/m², 20°C ambient temperature, 1m/s wind speed, AM 1.5 spectrum.

Please contact support@etsolar.com for technical support. The actual transactions will be subject to the contracts. This parameters is for reference only and it is not a part of the contracts. The specifications are subject to change without prior notice.

The connectors listed in the datasheets are for reference only and it is not a part of the contract. The connector we use for the customer's order is not limited to the types listed in the datasheet, which is subject to change without prior notice. The installers need to use the same connector type to PV system.